

# Caroma®

## Leda


Vitreous China 4.5/3 litre Dual Flush  
Wall Faced Box Rim Close-Coupled Toilet Suite



CI/SfB	(74.1)	g3
Date	April 2015	

Supersedes all previous issues

# 3.22.1





### Leda



A premium designed fully integrated close-coupled wall faced pan with box rim delivering a 4.5/3 litre dual flush. The **Leda** features smooth sides and concealed plumbing fittings, which allow for varying setouts. The pan connection system includes the patented Caroma Uni-Orbital® connector for increased installation flexibility. The Caroma Uni-Orbital® connector extends to any position up to a 25mm radius, unlike traditional connectors that only move backwards and forwards. The setout range is from 60mm – 220mm with a recommended setout of 140mm.

**Pan:** Leda 4.5 litre full flush box rim pan.

**Traps:** Universal trap for S or P-trap installations. 50mm vent option available.

**Cisterns:** Leda cistern – has a free fitting lid and is suitable for domestic and light commercial applications. Available with internal overflow. Standard back inlet.

**Vandal Resistant Conversion Kit** – A simple to install conversion is available for the standard mechanism to lock lid onto the cistern, recommended for use in heavy use commercial areas. Code No.750109.

Cistern inlet stop valve and inlet connection is concealed within the cistern and is included.

**Important: Working pressure minimum 30kPa to maximum 1000kPa flow pressure. Rain water tank compliant. Accurate wall setout for B.S.P. 1/2" Nipple water inlet connection is essential.**

**Fixing:** The cistern is fixed directly to the pan with a robust concealed base fixing system without the need for wall fixing.

**Seats:** The **Pedigree II** toilet seat or **Pedigree II** soft close toilet seat is provided as standard with the Leda suite. A quality solid section compression moulded toilet seat. Fitted with buffers and metal hinges.

**Colours:** White only.

**Installation:** The installation of the toilet suite shall be in accordance with the normal minimum drainline grade requirements in AS/NZS 3500.2.

**Dimensions:** All dimensions are in millimetres and are subject to normal manufacturing variations. Caroma pursues a policy of continuing improvement in design and performance of its products. The right is therefore reserved to vary specifications without notice.

